

PRECISION 2.5 VOLT MICROPOWER VOLTAGE REFERENCE

ZR4040-2.5

ISSUE 2 - NOVEMBER 1996

DEVICE DESCRIPTION

The ZR4040-2.5 uses a bandgap circuit design to achieve a precision micropower voltage reference of 2.5 volts. The device is available in small outline surface mount packages, ideal for applications where space saving is important, as well as packages for through hole requirements.

The ZR4040-2.5 design provides a stable voltage without an external capacitor and is stable with capacitive loads. The ZR4040-2.5 is recommended for operation between 60µA and 15mA and so is ideally suited to low power and battery powered applications.

Excellent performance is maintained to a suggested absolute maximum of 25mA, however the rugged design and 20 volt processing allows the reference to withstand transient effects and currents up to 200mA. Superior switching capability allows the device to reach stable operating conditions in only a few microseconds.


FEATURES

- Small-outline SO8 and SOT23 packages
- TO92 style package
- No stabilising capacitor required
- Typical T_c 30ppm/°C
- Typical slope resistance 0.4Ω
- 2% 1% and 0.5 % tolerance
- Industrial temperature range
- Operating current 60µA to 15mA
- Transient response, stable in less than 10µs

APPLICATIONS

- Battery powered and portable equipment.
- Metering and measurement systems.
- Instrumentation.
- Test equipment.
- Data acquisition systems.
- Precision power supplies.

SCHEMATIC DIAGRAM



CONNECTION TABLE

Pin	SO8	SOT23	E-LINE 3 pin R
1	N/C	-	G_{nd}
2	N/C	G_{nd}	V_R
3	N/C	V_R	-
4	G_{nd}	-	-
5	N/C	-	-
6	N/C	-	-
7	N/C	-	-
8	V_R	-	-
Pack	N8	F	R

see Connection Diagrams

ZR4040-2.5

ABSOLUTE MAXIMUM RATING

Reverse Current	25mA
Forward Current	25mA
Operating Temperature	-40 to 85°C
Storage Temperature	-55 to 125°C


Power Dissipation (T_{amb}=25°C)

SOT23	330mW
SO8	625mW
E-line, 3 pin (TO92)	500mW

SYMBOL	PARAMETER	CONDITIONS	LIMITS			TOL. %	UNITS
			MIN	TYP	MAX		
V _R	Reverse Breakdown Voltage	I _R =150μA	2.4875 2.475 2.45	2.5 2.5 2.5	2.5125 2.525 2.55	0.5 1 2	V
I _{MIN}	Minimum Operating Current			25	60		μA
I _R	Recommended Operating Current		0.06		15		mA
T _C †	Average Reverse Breakdown Voltage Temp. Co.	I _{R(min)} to I _{R(max)}		30	100		ppm/°C
R _S §	Slope Resistance			0.4	2		Ω
Z _R	Reverse Dynamic Impedance	I _R = 1mA f = 100Hz I _{AC} = 0.1 I _R		0.3	0.8		Ω
E _N	Wideband Noise Voltage	I _R = 1mA f = 10Hz to 10kHz		43			μV (rms)


$$† T_C = \frac{V_R \text{ Change} \times 1000000}{V_R \times \text{Temperature Change}}$$

$$§ R_S = \frac{V_R \text{ Change} (I_R \text{ (min) to } I_R \text{ (max)})}{I_R \text{ (max)} - I_R \text{ (min)}}$$




ZR4040-2.5


TYPICAL CHARACTERISTICS




Forward Characteristics




Temperature Drift




Slope Resistance v Current



Slope Resistance v Frequency






Transient Response ($I_R = 150\mu\text{A}$)



Transient Response ($I_R = 5\text{mA}$)

ZR4040-2.5

CONNECTION DIAGRAMS



Ordering Information			
Part Number	Tol%	Package	Partmark
ZR404005N825	0.5	SO8	ZR4040525
ZR404005F25	0.5	SOT23	25V
ZR404005R25	0.5	E-Line 3 pin R	ZR4040525
ZR40401N825	1	SO8	ZR4040125
ZR40401F25	1	SOT23	25M
ZR40401R25	1	E-Line 3 pin R	ZR4040125
ZR40402N825	2	SO8	ZR4040225
ZR40402F25	2	SOT23	25L
ZR40402R25	2	E-Line 3 pin R	ZR4040225